

a Darge www.alarge.com.tr

AGILE, ROBUST,
SMART LAB SYSTEM.
SUSTAINABILITY AND RESILIENCE.

MINI PLASTIC INJECTION MOULDING MACHINE

Standards

EN ISO 20430:2020 ISO 10724-1:1998 BS EN 201

The whole machine is small in size, light in weight, easy to move, install and use, suitable for one mold, 1–10 grams of product injection.



ALARGE ALIÇ AĞACI MAK. ELEK. AR-GE SAN. TİC. LTD. ŞTİ.

www.alarge.com.tr

Çifte Havuzlar Mah. Eski Londra Asfaltı Cd. YTÜ Teknopark D2 Blok No: 2B01 Davutpaşa – İstanbul/TÜRKİYE **Fax:** +90 212 278 61 33 **Mail:** info@alarge.com.tr

www.alarge.com.tr

+90 212 924 56 52

a Darge

TECHNICAL SPECIFICATIONS

- PLC control
- Servo motor driven system which can control more precision and accuracy
- Very quiet motor pump controlled by an inverter
- Cooling circuit
- PID temperature control
- 4 temperature control zones with differentiated mould temperature adjustment (moving and fixed half)
- Pressure control with electronic transducer
- Injection and clamp position controlled with linear transducers
- 7[□] touch screen control
- Proportional hydraulics
- Low running costs installed power 3 kW cooling approximately 120 l/h
- 60 cm³ Theoretical Shot Volume





PLASTIC PROCESSING:

- ✓ PE, PP, PVC, ABS, PET, PPRC, PC
- ✓ Horizantal style
- ✓ Full Automatic and Semi Automatic mode
- ✓ The touch screen to start and stop the machine, adjust settings and monitor progress in real time.
- ✓ Temperature tolerance band
- ✓ Hydraulic ejection with ejector return sensor
- ✓ Mold clamping system Unique crank arm mechanical structure system which can enhance the mold clamping force

